تاريخ:
شماره:
پيوست:

شرکت صنایع شیمیایی آذین بسپار سپاهان

(Pu Adhesive, Polyol, Saturated polyester)

تولید کننده انواع پلی ال ها، پلی استرهای اشباع، چسبهای پلی یورتان



APSPOL10S14A

These products are mostly solid at ambient temperature and have high wear, tear and mechanical resistance with high density.

- They are suitable for use in the production of artificial leather resins, coatings, water-based polyurethanes and coatings, and tpu elastomers.
- The solid percentage of this product is 100%.
- According to the customer's request, it can be provided with different molecular mass and different solid percentage.

packing:

This product can be presented in 220 kg galvanized barrels or 20 kg plastic containers.

The shelf life of this product is 12 months after production at a temperature of 25°C.

Product Code	Molecular weight	Hydroxyl value (mgKOH/g)	Acid value (mgKOH/g)	Water value (%)	Viscosity (cps)
APSPOL10S14A	1000	106 - 118	0.1 - 0.8	< 0.03	380 @ 60 °C

Add: Sejzy Industrial Zone, Isfahan, Iran

Tel: +983146412415-7 Fax: +983146412411

Web: www.apspolymer.com Email: info@apspolymer.com آدرس : شهرک منعتی بزرگ شرق اصفهان(سجزی)خیابان چهارم

شرقی – نبش فرعی پنجم – پلاک ۱۳ . .

تلفن: ۷–۴۶۴۱۲۴۱۵ فکس: ۳۱–۴۶۴۱۲۴۱۱

آدرس وب سایت : www.apspolymer.com یست الکترونیک : info@apspolymer.com