شرکت صنایع شیمیایی آذین بسپار سپاهان
(Pu Adhesive, Polyol, Saturated polyester)
تولید کننده انواع پلی ال ها، پلی استرهای اشباع، چسبهای پلی یورتان
سهامی خاص ثبت ۴۸۴۶۱

APSPOL20SEDTPAM

. This polyol is mostly liquid at ambient temperature and has an activity of 2.6-2.2

It has good mechanical properties and is mainly designed for the use of adhesives, . two-component coatings, hard and semi-hard foam, lubricants and concrete floors

The solid percentage of this product is 100% and it can be provided with different – solid percentage and molecular weight according to the customer's request

Product Code	Molecular weight	Hydroxyl value (mgKOH/g)	Acid value (mgKOH/g)	Water value (%)	Viscosity (cps)	Application
APSPOL20SEDTPAM	2000	54 - 56	0.5 - 0.8	< 0.03	1000 @ 60 ℃	adhesives, coating, elastomers

: Packaging

This product can be presented in 220 kg galvanized barrel or 20 kg plastic . containers

The shelf life of this product is 12 months after production at a temperature of .25°C

Add : Sejzy Industrial Zone, Isfahan, Iran
Tel : +983146412415-7
Fax: +983146412411
Web : www.apspolymer.com
Email : info@apspolymer.com

آدرس : شهرک صنعتی بزرگ شرق اصفهان(سجزی)خیابان چهارم شرقی – نبش فرعی پنجم – پلاک ۱۳
تلفن : ۷-۰۳۱-۴۶۴۱۲۴۱۵
فکس : ۰۳۱-۴۶۴۱۲۴۱۱
آدرس وب سایت : www.apspolymer.com
پست الکترونیک : info@apspolymer.com