



سهامی خاص ثبت ۴۸۴۶۱

شرکت صنایع شیمیایی آذین بسپار سپاهان

(Pu Adhesive, Polyol, Saturated polyester)

تولید کننده انواع پلی ال ها، پلی استرهای اشباع، چسبهای پلی یورتان

تاریخ:

شماره:

پیوست:

Fabric laminate adhesive Strong lamination resins PC: HHPMET2155

This product is a two-component thermoplastic polyurethane resin based on MDI and isoferon diisocyanate with excellent strength and flexibility suitable for laminating all types of textile, polymer and composite surfaces. This product is known as furniture laminate adhesive, high drying speed, waterproof and detergent. The viscosity and solid percentage of this product are adjusted in such a way that the consumer does not need to add diluent, however, if dilution is needed, you can use ethyl acetate, MEK, or toluene solvents.

TECHNICAL PROPERTIES :

Appearance. Slightly yellow transparent liquid

Solid content. 50%

Solvent. Ethyl acetate

Viscosity. 15000-25000 cp@25c

Tensile strength. 150-250 kg/cm³

Storage condition. 18 - 25 C

shelf life. 1 year

Packaging. 200 kg barrels

+ instructions:

Mix components A and B (Desmador n-65) in a ratio of 10: 1. After 5 minutes, if the viscosity of the adhesive is suitable, pour it into the pan of the machine and use it. Otherwise, use the said solvents for dilution. If the curing speed is faster, do not add the amount of hardener and consult with the company's experts to adjust the conditions or receive a catalyst.

Avoid contact of moisture with glue before curing.

Add : Sejzy Industrial Zone, Isfahan, Iran

Tel : +983146412415-7

Fax: +983146412411

Web : www.apspolymer.com

Email : info@apspolymer.com

آدرس : شهرک صنعتی بزرگ شرق اصفهان (سجزی) خیابان چهارم

شرقی - نبش فرعی پنجم - پلاک ۱۳

تلفن : ۰۳۱-۴۶۴۱۲۴۱۵-۷

فکس : ۰۳۱-۴۶۴۱۲۴۱۱

آدرس وب سایت : www.apspolymer.com

پست الکترونیک : info@apspolymer.com