شرکت صنایع شیمیایی آذین بسپار سپاهان
(Pu Adhesive, Polyol, Saturated polyester)
تولید کننده انواع پلی ال ها، پلی استرهای اشباع، چسبهای پلی یورتان
سهامی خاص ثبت ۴۸۴۶۱

Prepolymer NDP-101

modified MDI

This category of products includes prepolymers based on MDI with different reactivity speed.

Consumables:

It is used to make all kinds of sealants and sealants, paints, coatings and adhesives. The above product can be used directly as a cover and glue. These coatings have very good resistance to chemical stains and acid and alkaline conditions, as well as good waterproofing. One of the distinctive features of this product is its excellent softness and flexibility and good tensile properties, which make this product suitable for use in synthetic leather, paint, textile, shoe, bag, wood and metal coatings industries, etc.

Add : Sejzy Industrial Zone, Isfahan, Iran
Tel : +983146412415-7
Fax: +983146412411
Web : www.apspolymer.com
Email : info@apspolymer.com

آدرس : شهرک صنعتی بزرگ شرق اصفهان(سجزی)خیابان چهارم شرقی – نبش فرعی پنجم – پلاک ۱۳
تلفن : ۷-۴۶۴۱۲۴۱۵-۰۳۱
فکس : ۴۶۴۱۲۴۱۱-۰۳۱
آدرس وب سایت : www.apspolymer.com
پست الکترونیک : info@apspolymer.com

شرکت صنایع شیمیایی آذین بسپار سپاهان
(Pu Adhesive, Polyol, Saturated polyester)
تولید کننده انواع پلی ال ها، پلی استرهای اشباع، چسبهای پلی یورتان
سهامی خاص ثبت ۴۸۴۶۱

TECHNICAL PROPERTIES:

Product	**APSIPADR12T**
color	light yellow
solid content	100%
NCO %	3-22 (customer adjust)
Shelf life	6 months
Storage temp	15-25

Tips:

Do not dilute this product with thinner. The solid percentage and isocyanate percentage of this product can be adjusted according to the customer's needs. The drying time of the resin can be adjusted according to the customer's needs. Keeping this resin at a higher temperature will reduce its storage time and at a lower temperature it will crystallize. Consult the experts of this company for re-use after crystallisation.
The hardening time of this resin varies depending on the humidity and temperature of the environment.

Add : Sejzy Industrial Zone, Isfahan, Iran
Tel : +983146412415-7
Fax: +983146412411
Web : www.apspolymer.com
Email : info@apspolymer.com

آدرس : شهرک صنعتی بزرگ شرق اصفهان(سجزی)خیابان چهارم شرقی – نبش فرعی پنجم – پلاک ۱۳
تلفن : ۷-۴۶۴۱۲۴۱۵-۰۳۱
فکس : ۴۶۴۱۲۴۱۱-۰۳۱
آدرس وب سایت : www.apspolymer.com
پست الکترونیک : info@apspolymer.com