Rubber Flooring Adhesive

Rubber and plastic floors produced by special and unique methods, have high durability and consistency and are resistant to sun heat, special weather conditions and abrasion. In addition, these floors have a higher degree of hardness than foam floors and their degree of curing varies. This type of flooring is mostly used to prevent injuries to children and athletes in recreational and sports places.

TECHNICAL PROPERTIES:

APSADR116	
Color	Light Yellow
Viscosity	1500cp@25
Mixing Ratio	2/1-4/1
(ADR116/NDP100)	
Solid content	100%
Shelf life	2year
Storage temp	15-25c
Package	220Kg barrel

TECHNICAL PROPERTIES:

APSPM75	
Color	light brown
Viscosity	1500cp@25
Nco content %	7.5%
Solid content	85%
Shelf life	6month
Storage temp	15-25c
Package	220Kg barrel

Areas of application of this type of rubber flooring can be listed as follows:

– Places that need to withstand high pressure on the floor; Such as playgrounds, around sports fields, kindergartens, children's playgrounds, shock absorbers and industrial machines and machines, fitness clubs.

– Places that are highly prone to erosion, such as swimming pools.

– Places where it is not possible to change the floor, such as sports / recreation complexes.

These adhesives are also very flexible and are very useful in places with frequent vibrations and shocks, for example in construction work. From the interlocking of scrap tires milled with polyurethane adhesives, children's playground floors or floors installed on pedestrian bridges are produced and marketed.

Add : Sejzy Industrial Zone, Isfahan, Iran
Tel : +983146412415-7
Fax: +983146412411
Web : www.apspolymer.com
Email : info@apspolymer.com

آدرس : شهرک صنعتی بزرگ شرق اصفهان(سجزی)خیابان چهارم
شرقی – نبش فرعی پنجم – پلاک ۱۳
تلفن : ۷-۰۳۱-۴۶۴۱۲۴۱۵
فکس : ۰۳۱-۴۶۴۱۲۴۱۱
آدرس وب سایت : www.apspolymer.com
پست الکترونیک : info@apspolymer.com