



سهامی خاص ثبت ۴۸۴۶۱

شرکت صنایع شیمیایی آذین بسپار سپاهان

(Pu Adhesive, Polyol, Saturated polyester)

تولید کننده انواع پلی ال ها، پلی استرهای اشباع، چسبهای پلی یورتان

تاریخ:

شماره:

پیوست:

Tpu solvent elastomers

This range of products includes polyesters with very high molecular weight polyethers modified with MDI and isoforon diisocyanate. The applications of these products are very diverse and mostly for the use of adhesives and single-component and two-component polyurethane coatings.

+Available codes and applications:

_ KOL100

With a hardness of 95 shore A, suitable for molding and extrusion purposes, making fire pipes, etc.

Melting point 160 degrees, very high crystallization speed, 100% solid percentage, 1.5 hydroxyl number, 25 kg bag packaging

_ KOLET21

Suitable for hot label adhesive, compatible with a variety of color pigments and nitrocelluloses, very high adhesion to surfaces, especially PVC and Plast wood with a softening point of 60 degrees Celsius. Also suitable for shoe adhesive shoe uppers
Technical specifications are available in the section of industrial adhesives

_ KOL4626

Suitable for shoe glue of outsole and upper with softening temperature of 55 to 60 degrees Celsius

Technical specifications are available in the section of industrial adhesives

_ HHPMMI

Very high adhesion, hardness 55 to 60 shoreA, excellent flexibility, suitable for printing inks and making all kinds of coatings and special colors

60% solids, ethyl acetate solvent, low crystallization rate, viscosity of 1200 cp at 25 ° C, hydroxyl number 0.25

Add : Sejzy Industrial Zone, Isfahan, Iran

Tel : +983146412415-7

Fax: +983146412411

Web : www.apspolymer.com

Email : info@apspolymer.com

آدرس : شهرک صنعتی بزرگ شرق اصفهان (سجزی) خیابان چهارم

شرقی - نبش فرعی پنجم - پلاک ۱۳

تلفن : ۰۳۱-۴۶۴۱۲۴۱۵-۷

فکس : ۰۳۱-۴۶۴۱۲۴۱۱

آدرس وب سایت : www.apspolymer.com

پست الکترونیک : info@apspolymer.com



سهامی خاص ثبت ۴۸۴۶۱

شرکت صنایع شیمیایی آذین بسپار سپاهان

(Pu Adhesive, Polyol, Saturated polyester)

تولید کننده انواع پلی ال ها، پلی استرهای اشباع، چسبهای پلی یورتان

تاریخ:

شماره:

پیوست:

_ ET2180I70301

Suitable for furniture fabric laminate adhesive, special coatings on leather and rubber and synthetic leather, two-part printing ink,

Solid percentage 45%, ethyl acetate solvent, medium crystallization rate, viscosity 1200 cp at 25 degrees, hydroxyl number 4 mg koh / g, mixing ratio 10 to 1 with Desmador n-65 made by this company.

_ HHPMNI55

As a one-component polyurethane varnish and coating with very high adhesion, it is 15% of NC dry matter

Solid percentage 45, solvent of ethyl acetate and butyl acetate, surface drying speed 30 seconds, viscosity 1200 cp at 25 degrees, hydroxyl number almost zero

_ HHPET2155

As a binder, two-component composite printing, glue and top coat, two-component furniture fabric, special coatings on leather and rubber, etc., with excellent adhesion

Solid percentage 41%, ethyl acetate solvent, medium crystallization rate, viscosity 1000 to 11000 cp at 25 ° C, hydroxyl number 5 / . Mg koh per gram.

Attention:

All of the above products should be stored at a temperature above 18 degrees Celsius.

The above products have a shelf life of at least 6 months.

They are packed in 200 kg barrels.

In all products, Desmador N-65 made by this company can be used to increase strength and thermal resistance after consulting with the company's experts.

Add : Sejzy Industrial Zone, Isfahan, Iran

Tel : +983146412415-7

Fax: +983146412411

Web : www.apspolymer.com

Email : info@apspolymer.com

آدرس : شهرک صنعتی بزرگ شرق اصفهان (سجزی) خیابان چهارم

شرقی - نبش فرعی پنجم - پلاک ۱۳

تلفن : ۰۳۱-۴۶۴۱۲۴۱۵-۷

فکس : ۰۳۱-۴۶۴۱۲۴۱۱

آدرس وب سایت : www.apspolymer.com

پست الکترونیک : info@apspolymer.com